

BACKHOE Industrial Service

MS904

The aggressive, self-cleaning, flat tread provides high traction, excellent stability and durability in tough & demanding applications

FEATURES

- ✦ Excellent grip
- ✦ Wear & cut resistant tread compound
- ✦ Specially designed domed mud breakers for optimum self-cleaning
- ✦ Reduced vibration & increased stability
- ✦ Deep under tread for improved puncture resistance
- ✦ Protected side wall for increased cut resistance



SIZE	PR	TYPE	RIM WIDTH	LI / SR		TREAD DEPTH	SECTION WIDTH (SW)	OVERALL DIAMETER (OD)
17.5L-24 (460/70-24)	10	TL	W15L	144A8	in.	33/32	17.5	48.8
					mm	26.5	445	1241
17.5L-24 (460/70-24)	12	TL	W15L	149A8	in.	33/32	17.5	48.8
					mm	26.5	445	1241
17.5L-24 (460/70-24)	16	TL	W15L	156A8	in.	33/32	17.5	48.8
					mm	26.5	445	1241
19.5L-24 (500/70-24)	12	TL	W16L	151A8	in.	34/32	19.5	51.7
					mm	27.5	495	1314
19.5L-24 (500/70-24)	16	TL	W16L	157A8	in.	34/32	19.5	51.7
					mm	27.5	495	1314

Distributed by:

--