

BACKHOE Industrial Service

MS902

The aggressive, self-cleaning, flat tread provides high traction, excellent stability and durability in tough & demanding applications

FEATURES

- ✦ Excellent grip
- ✦ Wear & cut resistant tread compound
- ✦ Specially designed domed mud breakers for optimum self-cleaning
- ✦ Reduced vibration & increased stability
- ✦ Deep under tread for improved puncture resistance
- ✦ Protected side wall for increased cut resistance



SIZE	PR	TYPE	RIM WIDTH	LI / SR		TREAD DEPTH	SECTION WIDTH (SW)	OVERALL DIAMETER (OD)
15.5/80-24 (400/80-24)	12	TL	13.00	154A8	in.	35/32	15.5	50.0
					mm	28	394	1270
15.5/80-24 (400/80-24)	14	TL	13.00	156A8	in.	35/32	15.5	50.0
					mm	28	394	1270
15.5/80-24 (400/80-24)	16	TL	13.00	159A8	in.	35/32	15.5	50.0
					mm	28	394	1270
15.5/80-24 (400/80-24)	-	TL	13.00	163A8	in.	35/32	15.5	50.0
					mm	28	394	1270
16.5/85-24	12	TL	13.00	163A6 FREE 151A6 DRIVE	in.	35/32	16.4	52
					mm	28	417	1322
16.5/85-24	14	TL	13.00	165A6 FREE 153A6 DRIVE	in.	35/32	16.4	52
					mm	28	417	1322
16.5/85-24	16	TL	13.00	168A6 FREE 155A6 DRIVE	in.	35/32	16.4	52
					mm	28	417	1322

Distributed by:

--