

# SKID STEER

## MS906

**The aggressive, self-cleaning tread design & side wall protection provides high traction and durability in tough, demanding applications.**

### FEATURES

- ✦ Wear & cut resistant tread compound
- ✦ Self-cleaning, stepped tread
- ✦ Reduced vibration & increased stability
- ✦ Excellent grip and full flat profile
- ✦ Reinforced shoulder, side wall and bead for enhanced stability
- ✦ Deep under tread for improved puncture resistance



| SIZE       | PR | TYPE | RIM WIDTH | LOAD CAPACITY AT 10 KM/H |     | TREAD DEPTH | SECTION WIDTH (SW) | OVERALL DIAMETER (OD) |
|------------|----|------|-----------|--------------------------|-----|-------------|--------------------|-----------------------|
| 27x8.50-15 | 8  | TL   | 7.00      | 1305                     | in. | 18/32       | 8.7                | 26.9                  |
|            |    |      |           |                          | mm  | 14.5        | 221                | 682                   |
| 10-16.5    | 10 | TL   | 8.25      | 2135                     | in. | 21/32       | 10.7               | 30.2                  |
|            |    |      |           |                          | mm  | 16.5        | 271                | 768                   |
| 12-16.5    | 12 | TL   | 9.75      | 2865                     | in. | 25/32       | 13.0               | 32.8                  |
|            |    |      |           |                          | mm  | 20          | 331                | 834                   |
| 14-17.5    | 14 | TL   | 10.5      | 3875                     | in. | 33/32       | 14.2               | 36.2                  |
|            |    |      |           |                          | mm  | 26          | 360                | 920                   |
| 15-19.5    | 14 | TL   | 11.75     | 4565                     | in. | 33/32       | 15.3               | 40.2                  |
|            |    |      |           |                          | mm  | 26          | 389                | 1020                  |
| 15-19.5    | 16 | TL   | 11.75     | 4935                     | in. | 33/32       | 15.3               | 40.2                  |
|            |    |      |           |                          | mm  | 26          | 389                | 1020                  |

Distributed by: