

BACKHOE Industrial Service

MS903

The aggressive, self-cleaning, flat tread provides high traction, excellent stability and durability in tough & demanding applications

FEATURES

- ✦ Excellent grip
- ✦ Wear & cut resistant tread compound
- ✦ Specially designed domed mud breakers for optimum self-cleaning
- ✦ Reduced vibration & increased stability
- ✦ Deep under tread for improved puncture resistance
- ✦ Protected side wall for increased cut resistance



| SIZE | PR | TYPE | RIM WIDTH | LI / SR | | TREAD DEPTH | SECTION WIDTH (SW) | OVERALL DIAMETER (OD) |
|------------------------|----|------|-----------|---------|-----|-------------|--------------------|-----------------------|
| 18.4-26 (480/80-26) | 12 | TL | W16L | 156A8 | in. | 36/32 | 18.8 | 56.3 |
| | | | | | mm | 28.7 | 478 | 1430 |
| 18.4-26 (480/80-26) | 16 | TL | W16L | 162A8 | in. | 36/32 | 18.8 | 56.3 |
| | | | | | mm | 28.7 | 478 | 1430 |
| 16.9-28 (440/80-28) | 12 | TL | W15L | 152A8 | in. | 34/32 | 17.2 | 55.5 |
| | | | | | mm | 27.5 | 438 | 1409 |
| 16.9-28 (440/80-28) | 14 | TL | W15L | 155A8 | in. | 34/32 | 17.2 | 55.5 |
| | | | | | mm | 27.5 | 438 | 1409 |
| 16.9-30 (420/85-30) | 12 | TL | W15L | 153A8 | in. | 34/32 | 17.1 | 57.5 |
| | | | | | mm | 27 | 435 | 1460 |
| 16.9-30 (420/85-30) | 14 | TL | W15L | 156A8 | in. | 34/32 | 17.1 | 57.5 |
| | | | | | mm | 27 | 435 | 1460 |
| 18.4-30 (460/85-30) | 12 | TL | W16L | 158A8 | in. | 36/32 | 18.5 | 60.2 |
| | | | | | mm | 28.7 | 470 | 1530 |
| 18.4-30 (460/85-30) | 14 | TL | W16L | 160A8 | in. | 36/32 | 18.5 | 60.2 |
| | | | | | mm | 28.7 | 470 | 1530 |

MS903

NOTE

Distributed by: